



Genie has launched its new Z-62/40 articulating boom, an update of the Z-60/34. The new Z-62/40 comes with significant modifications and is available in all markets. Its working height has been increased from 18,4m to 18,9m and provides more horizontal outreach of 12,4m compared with the Z-60/34's 11m.

Stellar has unveiled its 3315 and 4421 telescoping boom cranes, with maximum lifting capacities of 1,4t and 1,8t, respectively. The units' CDT system uses multiple sensory indicators to engage and communicate with the operator when approaching maximum capacity.

Grading into corners

Mounted using the Bob-Tach system, the grader with Laser Mounting Kit and Laser receivers on the new Bobcat T650H tracked loader is part of a wide range of grading solutions from Bobcat based around the company's compact loaders and grader attachments.

The 274cm grader features a six-way blade, plus hydraulic side-shift of up to 33cm left or right.

It has four two-way hydraulic functions including left side up/down; right side up/down, blade rotation left/right and blade side shift left/right.

The hydraulic side-shift allows the blade to get further into corners in confined areas.



Bobcat

It also allows grading right up to an obstacle, such as a pole or structure inside a building,

side-shifting to get around it and then side-shifting back to continue to work. This mini-

mises the amount of manual labour needed to clear the area around these objects.

MARLBORO

CRANE HIRE



JOHANNESBURG: TEL: (011) 882 8301/2
FAX: (011) 882 8303
SECUNDA: TEL: (017) 634 8339
WEBSITE:

WWW.MARLBOROCRANE.CO.ZA